

CONTECH PLATINUM

Wall Putty

WHITE CEMENT BASED WATER RESISTANT WALL PUTTY



DESCRIPTION

CONTECH PLATINUM Wall Putty is made from white cement, imported polymers, fillers and others speciality chemicals. It gives smoother and stronger adhesion to the concrete / freshly plastered wall, minimizing paint cost and extend its durability. **CONTECH PLATINUM** Wall Putty gives tough, non absorbent and hard white finish, requiring no curing. Its superior water resistant property prevents the paint from flaking even if the walls are damp.

CONTECH PLATINUM Wall Putty seals minor cracks / crevices in the wall and gives smooth & even surface. The Putty being pure white and smooth, brings out the true tone / shade of expensive paint applied over it.

SALIENT FEATURES

1. Crack resistant.
2. Odourless and antifungal
3. Water resistant and can be applied on moist surface.
4. Fast drying.
5. Used for exterior and interior use.
6. Suitable for new and old surface.
7. Good bond strength.
8. Economical.
9. Bright white in colour, gives smooth and glossy finish surface.
10. High tensile, compressive and flexural strength than gypsum based POP.
11. Used on hollow blocks / concrete walls.
12. Does not contain lead, oil or toxic materials.

METHOD OF APPLICATION

Surface Preparation

Ensure the surface is free from dirt, grease, loose particles, and fungus before treating with **CONTECH PLATINUM** Wall Putty. The surface should be sufficiently wet before the putty is applied.

Mixing and application

CONTECH PLATINUM Wall Putty shall be slowly mixed with approximately 35-40% of clean water by volume to make a uniform paste. (Do not add putty in to water). It is advisable to mix **CONTECH PLATINUM** Wall Putty with mechanical mixer. Prepare putty which can be used within 2-3 hours.

CONTECH PLATINUM Wall Putty is then applied with a Putty knife on the prewetted surface in upward direction uniformly to a thickness of 1.5mm. After about 4-5 hours when the first coat is dry out, apply second coat with putty blade to a thickness of 1 mm in perpendicular direction of 1st coat.

Allow surface to dry completely for 3 days and remove any marks with emery paper of not less than 500 number to get a glossy finish. One or multiple coats may be required depending on the nature and imperfections of the surface.

COVERAGE

CONTECH PLATINUM Wall Putty will cover 2 to 2.5 sq.mtr/ kg/mm. The coverage can vary depending on the surface texture, method of application and wastage.

STORAGE / SHELF LIFE

CONTECH PLATINUM Wall Putty should be stored in dry place. Shelf life is 12 months under normal storing condition.

PACKING

CONTECH PLATINUM Wall Putty is available in 20 Kg / 40 Kg bags

PRECAUTIONS

Avoid contact with skin for prolonged period. Any contact with eye, wash immediately with plenty of water and seek medical attention. Though it contains non toxic materials but still care should be taken to avoid dust inhalation. Use rubber gloves while mixing as prolonged exposure to "Contech Platinum Wall Putty" may soften the skin and irritation may occur due to cement particles. Keep it away from the children.

Mfg By

®



A/3, Panchtirth Apartments, Nr. Mahalaxmi Cross Road,
Paldi, Ahmedabad-380 007. INDIA

Phone: +91-79-26631141, 65120580, Mo.: 098240 68278

Email : contechchemicals@hotmail.com,

info@contechchemicals.com

Web : www.contechchemicals.com

Chemists to the Building Industry

Important Note : Whilst the information and/or specification contained herein, are to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendation or suggestion made by us, as we do not have any direct control over its application.